

Repetidores

**ICOM**



www.pcimiami.com
+1 (305) 822-2258


PORTABLE COMMUNICATIONS, INC
"A Trusted Partner"

Icom America Systems

X↔BAND 50

BRIDGING THE GAP BETWEEN BANDS

Crossband Communications

Powerful Crossband Capability

- Full UHF and VHF interoperability; provides seamless inter-band communications. Inter-agency communications just got easier!
- 50 Watts VHF; 45 Watts UHF
- Local controlled operation; can also be used as a dual base unit (with optional mic)
- Feature rich; affordable price

Maximum Frequency Flexibility / Alpha Tag Your Channels

- 128 Memory channels with 8 memory banks per radio
- 8-Character alphanumeric display / easy to read

AC to DC Auto Select, 220/110/12V Capable

Power failure? Not a problem. The X-Band 50 is configured to auto switch from AC to DC (Batteries not included)

Compact Size

Set the X-Band 50 on a desktop, or mount it in a 19" industry standard rack.



Radios, controller, and power supply, all in one box. Dual broad-air fans keep the unit cool. 19" Rack mountable. Battery backup capable.



A clean rear panel design allows for easy setup and operation. An options connector allows for customized applications such as Interconnect, CWID, and more.



UHF



VHF



CY-5000 VHF
CY-6000 UHF

All-in-One, Plug and Play IDAS™ Digital + Analog Repeater



*Warehouses
Schools & Universities
Hospitals
Amusement Parks
Correctional Institutions
Sports Complexes
Corporate Campuses
Gaming Facilities
Hotels
Multi-plex Cinemas
Office Tower Security
Shopping Malls
...and many more applications*



The F3161D portables and F5061D mobile series are designed for the IDAS™ system.

Features:

- Selective call, group call, talk group ID
- Status call/request
- Radio check
- Radio stun/kill/revive
- Data call
- Digital voice encryption
- Emergency call
- Call alert
- Call log
- And more...



VHF AND UHF REPEATER

IC-FR5000 VHF REPEATER

IC-FR6000 UHF REPEATER

iDAS
COM DIGITAL ADVANCED SYSTEM



**Dual mode
Double
Channels**



IDAS digital/
analog FM

IDAS Trunking
(With UC-FR5000)

Two RF modules
in one unit (option)

50W output
25W full duty

5-Tone, DTMF
CTCSS, DCS

2U height
rackmount

32ch memory,
dot-matrix LCD

